

TRX250™

Serving faithfully as long-time best seller, the manual-shift TRX250™ continues to be a favourite choice. Credit its rugged features, get-it-done attitude and stylish looks, along with a strong-running 229cc OHV engine, electric starting and more.



Unique Features

TRX250™ features the high-performance cylinder head from the TRX250EX for increased performance.

An oil cooler is standard equipment, ensuring optimal engine temperatures under difficult operating conditions.

Uniquely designed floorboards, which allow the rider's feet to grip the footrests while keeping mud and debris away from the rider's feet.

Additional Features

- Lightweight, OHV air cooled 229cc engine is longitudinally mounted to allow direct driveshaft alignment to rear wheels for fewer frictional losses.
- Automatic cam-chain tensioner reduces maintenance
- Convenient electric starter with auxiliary recoil starter
- Five-speed transmission with reverse and automatic clutch
- Front and rear suspension has been upgraded for more comfortable all-day riding.
- Lightweight double-cradle steel chassis.
- Maintenance-free shaft drive routes power directly from the longitudinally mounted engine without inefficient directional changes.
- Ergonomically designed seating and control layouts provide a comfortable operating position for a wide range of rider sizes.
- Meet EPA and CARB emissions level.
- Large cargo racks front and rear allow payloads of 15 and 30 kilograms, respectively.
- Large, lightweight plastic fuel tank with 9 litre capacity

SPECIFICATIONS

Engine Type	229cc air-cooled OHV longitudinally mounted single-cylinder 4-stroke
Bore and Stroke	68.5 x 62.2mm
Carburation	20mm piston-valve
Ignition	AC-CDI with electronic advance
Starter	Electric with auxiliary recoil
Clutch	Automatic / Centrifugal
Transmission	5-speed with reverse
Drive	Direct rear enclosed driveshaft
Dimensions	1,905mm x 1,035mm x 1,070mm (LxWxH)
Wheelbase	1,131mm
Seat Height	793mm
Ground Clearance	150mm
Turning Ratio	2.5m
Fuel Capacity	9.1litre (inc 2.6ltr reserve)
Front Tyre	22 x 7-11 inch
Rear Tyre	22 x 10-9 inch
Front Suspension	Independent double-wishbone; 130mm of travel
Rear Suspension	Swingarm with single shock; 125mm of travel
Front Brake	Dual sealed hydraulic drum
Rear Brake	Sealed mechanical drum
Max Weight	175kg
Kerb Weight	199kg
Warranty	24 months