

TRX420FE

The Fourtrax 420 is a true mid-size all-round ATV with class-leading power, performance and efficiency.



Unique Features

With its rugged next-generation styling, the Honda Fourtrax 420 offers exceptional pulling power, all-weather easy starts and quick acceleration, delivered by a fuel-injected, liquid-cooled 420cc engine. It also features a beefy 5-speed gearbox. For stopping power to match, dual front hydraulic disc brakes with disc covers incorporate patented built-in scrapers that remove mud and snow from inside the front wheel. Easy to maintain and handle, the Fourtrax 420 is fun to ride with all the reliability you would expect from a Honda ATV.

Additional Features

- Rugged OHV liquid-cooled fuel-injected 420cc engine, delivers both economy and performance.
- Handlebar mounted Electric Shift Program (ESP) for quick push-button gear selection.
- Overhead-valve design provides compact engine dimensions for excellent ground clearance while maintaining a broad, easy-to-use powerband.
- Adjustable spring preload is now featured on all shocks to allow suspension tuning to match varying loads and riding conditions.
- New enclosed-axle type swingarm with optimized stiffness for improved toughness and durability, and excellent handling performance
- New rubber swingarm pivot bushings yield increased low-speed ride comfort and increased durability.
- New fuel pump is derived from Honda automobile technology. It mounts in the fuel tank for better heat isolation and offers increased filter life.
- Dual front hydraulic disc brakes and sealed mechanical rear drum brake for strong stopping power.
- New aggressively styled bodywork also provides better mud and water protection.
- Rear brake is now located inside the right rear wheel for improved durability and increased ground clearance.

SPECIFICATIONS

Engine Type	420cc liquid-cooled single cylinder, 4-stroke OHV longitudinally mounted engine.
Bore and Stroke	86.5mm x 71.5mm
Carburation	Keihin® PGM-FI, throttle bore size 34mm, body fuel-injection system
Ignition	Full-transistorised
Starter	Electric with auxillary recoil
Clutch	Multiplate wet clutch
Transmission	5-speed with reverse electric shift
Drive	4wd Direct drive-shafts, AP Suretrac™ torque sensing limited-slip differential with switchable 2wd/4wd
Dimensions	2,103mm x 1,205mm x 1,174mm (LxWxH)
Wheelbase	1,268mm
Seat Height	856mm
Ground Clearance	183mm
Turning Ratio	2.8m
Fuel Capacity	14.7 litre (inc 4.9ltr reserve)
Front Tyre	24 x 8 - 12 inch
Rear Tyre	24 x 10-11 inch
Front Suspension	Independent double-wishbone; 170mm of travel
Rear Suspension	Swingarm with single shock 170mm of travel
Front Brake	Dual hydraulic discs
Rear Brake	Sealed mechanical drum
Kerb Weight	278kg
Warranty	24 months